

WATER DISPENSER

AQA drink 40

PREMIUM FLOOR-STANDING UNIT IN AN ELEGANT DESIGN WITH LCD SCREEN





The elegantly designed grid-bound AQA drink 40 in brushed stainless steel looks particularly good. Film sequences or pictures can be played via an integrated LCD screen. As an additional design element, apart from the screen, the control buttons and the beverage dispenser are also backlit. The modern unit is ideal for use at trade fairs and exhibitions, at info points, in fitness centres or at the POS. The water dispenser is equipped with 3 water options. Depending on individual taste you can have still, cold or sparkling water at the push of a button. Due to the powerful ice bank cooling technology, the capacity of 30 l/h with cold/sparkling water can be kept constant even with larger water withdrawals. An integrated UVC lamp serves as a hygiene barrier from the outside at the water outlet. So that you can enjoy your daily water with hygienic safety. Inside the water dispenser, the filter, the CO₂ bottle as well as a waste water tank have space.

Filter technology for Magnesium Mineralized Water

The appropriate BWT AQA drink filter cartridge with patented BWT Magnesium Technology, transforms tap water into an enjoyable taste experience. For hygienic safety we recommend filters with an integrated ultrafiltration membrane that retains 99.9999% of bacteria and microplastics up to 0.001 mm.




OVERVIEW DATA

GENERAL INFORMATION		CA	CAS
ARTICLE NUMBER		825017	825016
TYPE		floor-standing model	
MATERIAL		stainless steel	
WATER OPTIONS		CA	CAS
AMBIENT, STILL		✓	✓
COLD, STILL		✓	✓
COLD, WITH CO2		-	✓
HOT		-	-

TECHNICAL DATA

OPERATING CONDITIONS		CA	CAS
WATER DELIVERY AT ROOM TEMPERATURE, STILL	l/h	120	120
WATER DELIVERY COLD, STILL CO2	l/h	30 -	30 30
WATER DELIVERY HOT	l/h	-	-
WATER TEMPERATURE COLD*	°C	3-10	3-10
WATER TEMPERATURE HOT	°C	-	-
FLOW SPEED	l/min	>2	>2
MAX. COOLING POTENTIAL	W	100	100
PERFORMANCE COMPRESSOR	HP	1/12	1/12
INLET WATER PRESSURE recommended max.	bar	3 5	3 5
CO2 PRESSURE recommended max.	bar	3.5 4	3.5 4
COOLING TECHNOLOGY COOLANT		Ice Bank R134a (R600 optional)	Ice Bank R134a (R600 optional)
LEAKAGE PROTECTION		yes	yes
CONNECTIONS		CA	CAS
MAINS VOLTAGE -FREQUENCY	V Hz	220-240 50	220-240 50
DRINKING WATER CONNECTION	mm	8	8
CO2 CONNECTION	mm	-	8
WASTE WATER CONNECTION/-TANK		optional	optional
DIMENSIONS & WEIGHTS		CA	CAS
WATER DISPENSER DIMENSIONS W x H x D	cm	40 x 131 x 41	40 x 131 x 41
TAPPING HEIGHT	cm	30.8	30.8
NET WEIGHT, WATER DISPENSER	kg	34	37
GROSS WEIGHT, WATER DISPENSER	kg	39	42

* at 20 °C inlet temperature

PROVEN QUALITY:  RoHS



BWT water+more GmbH
 Walter-Simmer-Straße 4, A-5310 Mondsee
 ☎ +43 (0) 800 800 555
 ✉ aqadrink@bwt.com

bwt.com