

* **SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- **1.1 Product identifier**
- **Trade name:** **Benamin Quick Granulat 25 kg**
- **CAS Number:**
51580-86-0
- **EC number:**
220-767-7
- **Index number:**
613-030-01-7
- **1.2 Relevant identified uses of the substance or mixture and uses advised against -**
- **Application of the substance / the mixture** Water disinfectant
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
BWT AG
Walter Simmer Straße 4
A - 5310 Mondsee
AUSTRIA
Tel.: +43/6232/5011-0
Fax: +43/6232/4058
email: office@bwt.at
- **Further information obtainable from:**
Abteilung F&E - Chemikalienbeauftragter
Tel.: +43/6232/5011-1427
email: msds-info@bwt-group.com
- **1.4 Emergency telephone number:**
Vergiftungsinformation Wien
Tel.: +43/1-406 43 43

 * **SECTION 2: Hazards identification**

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The substance is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS07



GHS09

- **Signal word** Warning

(Contd. on page 2)

Trade name: Benamin Quick Granulat 25 kg

(Contd. of page 1)

- **Hazard-determining components of labelling:**
troclosene sodium, dihydrate
- **Hazard statements**
H302 Harmful if swallowed.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H410 Very toxic to aquatic life with long lasting effects.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P273 Avoid release to the environment.
P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Additional information:**
EUH031 Contact with acids liberates toxic gas.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.1 Chemical characterisation: Substances**
- **CAS No. Description**
51580-86-0 troclosene sodium, dihydrate
- **Identification number(s)**
- **EC number:** 220-767-7
- **Index number:** 613-030-01-7

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
Rinse out mouth and then drink plenty of water.
Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

GB

(Contd. on page 3)

Trade name: Benamin Quick Granulat 25 kg

(Contd. of page 2)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Water
- **For safety reasons unsuitable extinguishing agents:** Extinguishing powder
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.
- **Additional information**
Collect contaminated fire fighting water separately. It must not enter the sewage system.

* SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Avoid formation of dust.
Keep away from ignition sources.
Ensure adequate ventilation
Mount respiratory protective device.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

* SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Store in cool, dry place in tightly closed receptacles.
Keep away from heat and direct sunlight.
- **Information about fire - and explosion protection:**
The product is not flammable.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
- **Information about storage in one common storage facility:**
Store away from reducing agents.
Store away from foodstuffs.
Do not store together with acids.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

* SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)

Trade name: Benamin Quick Granulat 25 kg

(Contd. of page 3)

· 8.1 Control parameters
· Ingredients with limit values that require monitoring at the workplace:
51580-86-0 troclosen sodium, dihydrate

WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
-----	---

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls
· Personal protective equipment:
· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

Filter P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Synthetic rubber gloves

PVC gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:


Tightly sealed goggles

SECTION 9: Physical and chemical properties
· 9.1 Information on basic physical and chemical properties
· General Information
· Appearance:
Form: Granulate

Colour: White

· Odour: Like chlorine

· Odour threshold: Not determined.

· pH-value at 25 °C: 6

· Change in condition
Melting point/freezing point: 250 °C

Initial boiling point and boiling range: Undetermined.

(Contd. on page 5)

Trade name: Benamin Quick Granulat 25 kg

(Contd. of page 4)

· Flash point:	Not applicable.
· Flammability (solid, gas):	Product is not flammable.
· Ignition temperature:	250 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Not determined.
· Explosive properties:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapour pressure:	Not applicable.
· Density:	Not determined.
· Bulk density at 20 °C:	1000 kg/m ³
· Relative density	Not determined.
· Vapour density	Not applicable.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water at 25 °C:	250 g/l
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
Organic solvents:	0.0 %
Solids content:	100.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
 Strong exothermic reaction with acids.
 Acts as an oxidising agent on organic materials such as wood, paper and fats.
 Contact with acids releases toxic gases.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Chlorine

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
 Harmful if swallowed.

 · **LD/LC50 values relevant for classification:**
51580-86-0 troclosen sodium, dihydrate

Oral | LD50 | 1400 mg/kg (rat)

(Contd. on page 6)

Trade name: Benamin Quick Granulat 25 kg

(Contd. of page 5)

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Very toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Very toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
 - **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
 - **European waste catalogue**
- | | |
|-----------|---|
| 16 09 04* | oxidising substances, not otherwise specified |
|-----------|---|
- **Uncleaned packaging:**
 - **Recommendation:** Disposal must be made according to official regulations.
 - **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- **14.1 UN-Number**
- **ADR, IMDG, IATA** UN3077

(Contd. on page 7)

Trade name: Benamin Quick Granulat 25 kg

(Contd. of page 6)


· **14.2 UN proper shipping name**
 · **IMDG, IATA** ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
 SOLID, N.O.S. (troclosene sodium, dihydrate)

· **14.3 Transport hazard class(es)**
 · **ADR, IATA**



· **Class** 9 Miscellaneous dangerous substances and articles.
 · **Label** 9

· **IMDG**



· **Class** 9 Miscellaneous dangerous substances and articles.
 · **Label** 9

· **14.4 Packing group**
 · **ADR, IMDG, IATA** III

· **14.5 Environmental hazards:**
 · **Special marking (ADR):** Symbol (fish and tree)
 · **Special marking (IATA):** Symbol (fish and tree)

· **14.6 Special precautions for user** Warning: Miscellaneous dangerous substances and articles.
 · **Danger code (Kemler):** 90
 · **EMS Number:** F-A,S-F
 · **Stowage Category** A
 · **Stowage Code** SW23 When transported in BK3 bulk container, see 7.6.2.12 and 7.7.3.9.

· **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **ADR**
 · **Limited quantities (LQ)** 5 kg
 · **Excepted quantities (EQ)** Code: E1
 Maximum net quantity per inner packaging: 30 g
 Maximum net quantity per outer packaging: 1000 g
 · **Transport category** 3
 · **Tunnel restriction code** -

· **UN "Model Regulation":** Void

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
 · **Directive 2012/18/EU**
 · **Named dangerous substances - ANNEX I** Substance is not listed.
 · **Seveso category E1** Hazardous to the Aquatic Environment
 · **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t

(Contd. on page 8)

Trade name: Benamin Quick Granulat 25 kg

(Contd. of page 7)

- *Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t*
- *15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.*

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Acute Tox. 4: Acute toxicity – Category 4

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

- *** Data compared to the previous version altered.**