



Options

- Connection kit for optimal performance
- Trolley

Why BWT bestsoft 11?

- Protects machines optimally from calcification
- Simplex soft water plant in compact design
- Fully automatic and simple to operate
- More output and less salt consumption by proportional salting process
- Prefabricated and assembled in the factory for simple installation and start-up
- Extended digital control system for maximum performance and efficiency
- Rotary valve for higher safety for operations

Nominal connection width (external thread)	BSP	34" (DN 20)	
Nominal flow according to EN 14743	l/h	1.440	
Operational pressure (min./max.)	bar	1,0 / 8,0	
Pressure loss at nominal flow according to EN 14743	bar	1,0	
Quantity of ion exchange resins	I	10	
Nominal capacity	m³ x °dH	26	
Nominal capacity	mol	4,6	
Reserves of regenerating agent in the cabinet	kg	12	
Salt consumption per regeneration	kg	1,5	
Water consumption per regeneration	I	85	
Temperature of water and surrounding (min./max.)	°C	5/30, 5/40	
Type of protection	IP	51	
Power connection	V/Hz	230 / 50	
Electrical power input	W	15	
Connection height for hard water inlet and soft water outlet	mm	403	
Channel connection (min.)	DN	50	
Measurements (without rolls): width, depth, hight (WxDxH)	mm	270 x 480 x 532	
Operative weight, approx.	kg	40	
Article No.	SS1	SS11X01A00	
EAN-Code	42502	4250266704006	

Attention should be paid to local installation instructions, general guidelines, general hygiene conditions and technical data.

Headquarters:

BWT water + more GmbH

Walter-Simmer-Straße 4 A-5310 Mondsee Phone: +43/6232/5011-0 Fax: +43/6232/4058 kundenservice.wm@bwt-group.com

BWT water + more Deutschland GmbH

Spiegelgasse 13 D-65183 Wiesbaden Phone: +49/611/58019-0 Fax: +49/611/58019-22 info@water-and-more.de

BWT UK Ltd.,

water+more division BWT House, The Gateway Centre Coronation Road High Wycombe HP12 3SU Phone: +44 (0)1494 838128 Fax: +44 (0)1494 838104

