

AQA drink Pro 60

- » Capacity of 60 l/h cold/sparkling water or 26 I/h hot water
- » Water options (4 per each unit): still, cold still, mild sparkling, sparkling or hot
- » Programmable glass and carafe filling
- Bluetooth, WiFi and App for device management
- » Integrated filter capacity monitoring
- » Version as a table-top or stand-alone unit















Innovative technology, hygienic safety and perfect taste at its best

Experience a whole new world in the field of grid-connected water dispensers with the AQA drink Pro 60. Equipped with an innovative technology concept and a clever hygiene concept paired with the proven BWT filter technology, you can enjoy your daily water in its best form. The device is available as a cold or hot water version in the colours black or white. An optional CO2 monitor is available for monitoring the CO2 cylinder content.

Filter technology for magnesium mineralized water

The appropriate BWT AQA drink filter cartridge with patented BWT Magnesium Technology, transforms tap water into an enjoyable taste experience. For hygienic safety, we recommend filters with an integrated ultrafiltration membrane that retains 99.9999 % of bacteria and microplastics down up to 0.001 mm.

State-of-the-art UV LED technology

An UV reactor at the water outlet prevents the system from being contaminated by bacteria that could reach the water outlet from external influences. The UV reactor is automatically activated when ambient or cooled, still water is dispensed. Additionally, the UV reactor activates automatically at regular intervals, to prevent recontamination.



The boiler (pro 60 hot only)

The BWT AQA drink Pro 60 HOT protects the boiler from limescale deposits with integrated, patented limescale protection technology. Limescale buildup in the boiler is prevented by minimally lowering the pH value of the supply water using CO₂ from the carbon dioxide bottle. As a result, the appliance is better protected and requires less maintenance.

The BWT mobile apps for even more user-friendliness

The BWT AQA drink Pro 60 is equipped with a mobile App support both for users and for maintenance and monitoring, making it even more user-friendly.

BWT Best Water Home - for users



- » Touchless operation of the water dispenser via NFC
- » Selection of desired water option and quantity via the mobile phone
- » Minimizes bacterial contamination on the unit

This is a purely offline application. No data is transferred to BWT.

BWT Best Water Professional - for professional device management

Makes the water dispenser IoT-enabled and facilitates maintenance and monitoring for the operator:



- » Step-by-step guide for easy installation and configuration
 - Setting of filter type and filter capacity
 - Setting water temperatures
 - Setting filling quantity (glass, carafe, cup, pot)
- » Step-by-step guide for easy cleaning and disinfection
- » Real-time function and error overview via a debug menu
- » Fleet management (or via the web page bfilter.bwt.com)
- » Detailed statistics (or via the web page bfilter.bwt.com)

Trained users can use the app in combination with the bFilter platform. It is an online application, which works with an available WiFi network only.



Product information



with push buttons

Technical data		PRO 60	PRO 60 HOT
Item number - Water dispenser BLACK		125548052	125546898
Item number - Water dispenser WHITE		125548053	125546901
Item number - Cabinet BLACK		125546900	
Item number - Cabinet WHITE		125546902	
Ambient, still		+	+
Cold, still	*	+	+
Cold, mild sparkling	Ö	+	-
Cold, sparkling	Ö	+	+
Hot	٦	-	+
Water output ambient	l/h	120	
Water output cold still/CO₂*	l/h	60	
Water output hot	l/h	-	26
Water temperature cold	°C	4 - 12	
Output speed	l/min	2	
Number of users		up to 100	
Water inlet pressure recommended/max.	bar	3.5 / 5	
CO₂ pressure recommended/max.	bar	4 / 5.5	
Cooling technology/Coolant		Cast aluminium block / R290 (80 g)	
Leakage protection		yes	
Pump type		Rotary vane pump	
Power supply	V/Hz	230 / 50-60	
Maximum power consumption	W	480	2460
Carbonator capacity	1	C).7
Water Inlet pipe	inch	5/16" - 8 mm	
CO ₂ Inlet pipe	inch	1/4"	
Waste water connection/tank		optional	
Table-top unit dimensions W x H x D	mm	275 x 455 x 460	
Stand-alone unit dimensions W x H x D	mm	275 x 1.380 x 460	
Tap hight	mm	270	
Table-top unit	kg	37	41
Weight stand-alone unit	kg	53	57
3 • • • • • • • • • • • • • • • • • • •	5		

Operation **UV-LED** reactor at the water outlet for hygienic safety Ш **Drip tray** Space for AQA drink filtration cartridge, CO2 cylinder and waste water tank









^{*} at standard room conditions (approx. 20 °C)